







93 S Railroad Avenue Unit C Bergenfield NJ 07621 USA www.enapart.com sales@enapart.com



Via del Canneto 35. Borgosatollo, Brescia - Italia www.enapart.it vendite@enapart.it



Barbaros Mah. Ihlamur Bul. Ağaoğlu My Newwork No:3/15 Ataşehir / İstanbul www.enapart.net satis@enapart.net



PRIVADA 10 B SUR #3908 COL. ANZUREZ, C.P. 72530, PUEBLA, PUE www.enapart.com.mx sales@enapart.com.mx



Friedrich-Ebert-Anlage 36, 60325 Frankfurt am Main, Germany www.enapart.de anfrage@enapart.de



4 boulevard Carnot, 95400 villiers-le-bel, Paris, France www.enapart.fr sales@enapart.fr



65049, ОДЕСА, ВУЛИЦЯ ІВАНА ФРАНКА, БУДИНОК 55, ПОВЕРХ 3 www.enapart.com.ua sales@enapart.com.ua



MUNICIPIUL BUCUREŞTI, SECTOR 3, B-DUL BASARABIA, NR.250, CORP P+5 Hempstead, HP1 3AF , United Kingdom www.enapart.ro sales@enapart.ro



〒584-0023 大阪府富田林市若松町 東2丁目2番16号 www.enapart.co.jp sales@enapart.co.jp



PLAZA NUESTRA SEÑORA DE LAS NIEVES 12 ,LOCAL ,50012,ZARAGOZA www.enapart.es ventas@enapart.es



Складова база "Онгъл", Склад А2, п.к. 4006, гр. Пловдив, България www.enapart.bg sales@enapart.bg



3 Austin Mews, High Street, Hemel www.enapart.co.uk sales@enapart.co.uk





Keyence

Enapart always strives to provide the competitive prices and timings of supplies for its customers. We sell only original equipment and spare parts, although we are not always the official distributor or manufacturer's dealer. All displayed trademarks and part numbers are the property of their respective owners.

BRAND'S PRODUCTS

Product	Description
<u>LV-N11P</u>	•
<u>AP-31P</u>	Drucksensor für Unterdruck
AP-C33W	Digital Pressure Sensor
<u>BL-1300</u>	
<u>BL-U2</u>	(Power supply for bar code reader DC power supply)
<u>CA-CH10</u>	Camera Cable 10-m for High-Speed Camera
<u>CA-D5</u>	
<u>CA-DBW5</u>	LIGHT
<u>CA-DC100</u>	LED lighting control unit 2 terminals (PWM) for LED lighting
CA-DC21E	LED Illumi-Controller
<u>CA-LH8</u>	Camera lens
<u>CA-MP81</u>	Monitor
<u>CV-200C</u>	Digital 2-million-pixel Color Camera
<u>CV-200M</u>	
<u>CV-5501P</u>	High-speed image processing system, image processing controller
CV-X100FP	Control Unit (Full Pack)
CV-X150RP	Easy Setup Machine Vision System
<u>CZ-41</u>	RGB Digital Fiber Sensor Small Beam Spot
<u>CZ-H32</u>	Reflective Sensor Head
<u>CZ-H37S</u>	Reflective Sensor Head with Shine Cancellation, Small Spot
<u>CZ-H52</u>	
<u>CZ-K1P</u>	Digital RGB Sensor, Amplifier: Main Unit, PNP
CZ-V21AP	Smart RGB Digital Sensor
<u>EH-614A</u>	sensor
ES-M1P	Proximity Sensor, Amplifier: DC Type, Main, Unit, PNP
EZ-8M	proximity sensor 3 wire
<u>F-3HA</u>	Fokus-Linse
<u>FS2-60P</u>	fiber optic amplifier
<u>FS-M1P</u>	Fiber optic measuring amplifier
<u>FS-N12CP</u>	
<u>FS-V21R</u>	Fiber Amplifier, Cable Type, Main Unit, NPN
<u>FS-V21RP</u>	PNP Digitaler Anzeige
FS-V31CP	
<u>FS-V31P</u>	Fiber Optic Sensor
<u>FU-38V</u>	
<u>FU-10</u>	Reflective fiber unit





Product	Description
<u>FU-12</u>	Fiber Unit ThruBeam, Wide Area Beam 2M
FU-35FA	Reflective Fibre Unit
FU-35FZ	
FU-35TG	Sensor
FU-40	
FU-52TZ	Fiber Optic Sensor
FU-67 TZ	•
FU-67 V	
FU-68	reflective light guide device
<u>FU-77</u>	Transmitting light guide device
<u>FU-77G</u>	Fest u. flexibel, Armiert
FU-77V	
GT2-71MCP	Amplifier Unit, Analog Output Type PNP
<u>GT2-71P</u>	High precision digital contact sensor
<u>GT2-A12</u>	
<u>GT2-H12</u>	High-precision Contact Dig. Sensor
<u>GT2-H32</u>	Sensor Head
<u>GT-71AP</u>	
<u>GT-H10</u>	Sensor head with 10 mm contact distance
<u>GV-H130</u>	probe
<u>IB-1000</u>	
<u>IG-028</u>	Sensor Head
<u>IG-1000</u>	Multi-Purpose CCD Laser Micrometer
<u>IL-065</u>	Keyence LASER-Wegmess-Sensor
<u>IL-1000</u>	
<u>IL-1050</u>	Keyence IL-1050
<u>IL-300</u>	CMOS Multifunctional analog laser sensor (sensor head)
<u>IL-600</u>	Messkopf
<u>IM-6015</u>	Measurement head
<u>IM-6025</u>	Measurement head, 1" 6.6 mega
<u>IV-500CA</u>	Vision Sensor Standardmodell Farbe OF Typ
<u>IV-M30</u>	Vision-Sensor Touch Panel Intelligenter Monitor
<u>LJ-G080</u>	
<u>LJ-G5001</u>	2D Laser Displacement Sensor
<u>LJ-GC5</u>	2D Laser Displacement Sensor LJG cable 5m
<u>LJ-H1W</u>	2D Laser Displacement Sensor Setting Software
<u>LK-G152</u>	[CCD Laser Wegmeßsystem]
<u>LK-G402</u>	CCD Laserwegmesssystem / Messkopf +/- 400mm, 100mm, Punkttyp, Laser class 2
<u>LR-TB5000CL</u>	
<u>LS-5001</u>	CONTROLOR HIGH SPEED LASER MICROMETER
LS-5041 (second hand)	Laser Micrometer System
<u>LS-7030</u>	
<u>LS-C3A</u>	Lazer sensor cable
<u>LV-21AP</u>	Amplifier Unit, Main Unit, PNP





Product	Description
<u>LV-B301</u>	mounting bracket
<u>LV-H32</u>	Digital Laser Sensor, Reflective Head:Spot, Adjustable
<u>LV-H42</u>	Reflective Sensor Head
<u>LV-H62</u>	Digital laser sensor head retro-reflective
<u>LV-S31</u>	OPTICAL SENSOR
<u>LV-S62</u>	Retro-reflective measuring head area type
<u>OP-51612</u>	LENS ADAPTER
<u>OP-76874</u>	A mounting bracket for the GT-measuring head
<u>OP80616</u>	RS232C CONVERSION CABLE
<u>OP-86935</u>	Horizontal Mounting Bracket
<u>OP-87057</u>	IL Sensor Head Cable
<u>OP-87353</u>	Control Cable
<u>OP-87354</u>	Autofocus/Compact 1D/2D Code Reader Control Cable (5m)
<u>OP-87359</u>	Ethernetkabel
<u>OP-87360</u>	Compact 2D Code Reader Ethernet Cable (5m)
<u>OP-87436</u>	Standard Vision Sensor
<u>OP-87441</u>	Power I/O cable (5 m)
<u>OP-87773</u>	
PZ2-62	Built-in Amp.Photo.Sensor, Reflective
<u>PZ2-62P</u>	
<u>PZ-51L</u>	Built-in Amp.Photo.Sensor Thrubeam
PZ-G41N	Photoelectric sensor
PZ-G42N	Self-Contained Photo Sensor
PZ-G61CP	Photoelectric sensor
<u>PZ-M52P</u>	
<u>PZ-V71P</u>	SENSOR/PHOTOELECTRIC
SL-V36H	Safety light curtain, hand protection scope 745mm Customs tariff number 85371099
<u>SR-751</u>	Code Reader
<u>SZ-04M</u>	
<u>SZ-P5PM</u>	LAZER SCAN SENSOR CABLE
<u>FU-43</u>	Flächenerkennung
<u>SR-1000W</u>	Autofocus 1D and 2D Code Reader, Wide-field type
LR-ZB250AP	Self-Contained Laser Sensor, w/ I-Datum, 250mm range, PNP
<u>TM-006</u>	2D MICROMETER, Sensor Head (6mm)
<u>LS-9006</u>	CMOS/GaN-LED Micrometer, (SENSOR HEAD)
<u>CB-A2</u>	Head-Controller Cable
LR-ZB250CN	
<u>OP-87059</u>	Keyence OP-87059
<u>PZ-V72</u>	Self-Contained Photo SW, Reflective 900mm, M8-Con
<u>PZ–M51</u>	Self-Contained Photo SW, 10M Thrubeam Type
<u>FU-35TZ</u>	Reflective Fibre Unit
P/N: 16100, Type: EH-302	sensor head
<u>OP-84297</u>	SJ montagehalterung
<u>SJ-C2H</u>	10pin-10-pin Kabel fuer SJ-H36A





Product	Description
FS-N15CP	Fiber Amplifier, M8 Connector Type, PNP
<u>OP-87153</u>	Electrode unit
<u>OP-51607</u>	STATIC ELIMINATOR (ELECTRODE PROBE)
<u>GV-H45</u>	Sensor Head Short-distance Type
<u>GV-21P</u>	
FS-T1P	Sensor
LS-5041R +LS-5041T	
CA-CN10R	Cable, 10 meters
<u>LJ-G030</u>	2D Laser Displacement Sensor
<u>FU-31</u>	sensor head
<u>IV-500MA</u>	Sensor, Standard distance, Monochrome, Automatic focus model
<u>PZ-42P</u>	Built-in Amp.Photo.Sensor Short Range, PNP
<u>OP-87457</u>	Vision Sensor Ethernet Cable
FD-M100ATP	Electromagnetic Flow Sensor PNP 5 to 100 Liter
<u>SZ-01S</u>	Safety Laser Scanner
<u>CZ-H35S</u>	Smart RGB Digital Sensor Reflective Luster-cancel
<u>CZ-11</u>	RGB Digital Fiber Sensor Spot Adjustable Side-View
<u>IM-6225</u>	
FS-N12P	Fiber Amplifier Cable Type, Expansion Unit, PNP 12
XG-8802P (Japan only product, alternative XG- 8802P)	High Speed Kameracontroller
CA-EC80	High-Speed,High-Capacity Controller
<u>CA-CN5</u>	Cable
<u>XG-S035MH</u>	Flexible Image Processing System
<u>XG-S035MU</u>	Flexible Image Processing System
<u>CA-LS16</u>	Compact Vision Sensor
XG-H8NE1 (Japan only product, alternative is XG- H8NE2)	Vision Editor Software Development
<u>CA-LH50</u>	
<u>XG-8802P</u>	Processing System
XG-H8NE2	Vision Editor Software
<u>SJ-M021G</u>	STATIC ELIMINATO
<u>SJ-M201</u>	STATIC ELIMINATOR
<u>SJ-U2</u>	AC ADAPTOR
<u>LV-S41</u>	Digital Laser Sensor Head
<u>CZ-12</u>	RGB Digital Fiber Sensor
<u>VT3-V6H</u>	PROGRAMMABLE OPERATION DISPLAY
<u>EG-547W</u>	Verstärker Toleranzeinstellung FNC
<u>EH-402</u>	Nicht abgeschirmt Meßkopf
<u>SH-416</u>	Meßkopf
<u>FU-20</u>	Digitale Lichtleitersensor
<u>FU-41TZ</u>	
<u>FU-49X</u>	Fiber Unit Reflective, High-Flex, 1M
<u>FD-M5ATP</u>	Electromagnetic Flow Sensor
<u>VT-H5G</u>	PC SOFTWARE FOR VT SERIES





Product	Description
<u>FU-66Z</u>	Reflective Fiber Unit
<u>SH-816</u>	Keyence
<u>TM-040</u>	Optical measuring instrument
<u>TM-3001P</u>	Non optical measuring instrument
<u>TM-H1</u>	PC SOFTWARE
<u>FU-6F</u>	reflective light guide device
<u>FU-67</u>	FU-67 Fest you. flexible
<u>IV-150MA</u>	
<u>IV-D10</u>	
<u>FU-77TZ</u>	Fiber Unit Thrubeam
<u>FS-V1</u>	
PZ-G41CB	Photoelectric Sensor
GT2-H12K	Sensor Head, High-precision Type
<u>OP-87440</u>	Vision Sensor Control Cable
<u>OP-87907</u>	Vision Sensor
<u>SJ-F2500</u>	Static Eliminator
SJ-F300	Controller for static blower
<u>CA-D10R</u>	
CA-DBR34H	LED Illumination Unit
CA-LF34R	Red BP filter
CA-LHR8	Lens
CA-SD4G	ULTRA-HI-SPEED VISION SYSTEM
CA-CN10X	Ext. cable for std camera
<u>OP-51657</u>	Connection cable
<u>FS-V11</u>	Lichtleiter-Messverstärker
<u>PZ-V32P</u>	
<u>FU-84C 5M</u>	Fiber Unit ThruBeam
<u>F2</u>	Long Range Lens
<u>SJ-F5500</u>	Static Eliminator
<u>SJ-H036A</u>	Static Eliminator
<u>SJ-C2U</u>	Static Elimination System
MS2-H50	Switching Power Supply
CV-X272AP	High-Speed, High-Capacity Controller
CA-CH5	
CA-DC30E	LED Illumi-Controller LumiTrax type
<u>CA-D5X</u>	Cable 5M for LumiTrax Light
CA-DRW10X	LED Illumination Unit LumiTrax,Ring Type,White,14
<u>CA-LH16</u>	C Mount Lens(16mm) High-Reso, Low distortion
CA-HX048C	470k Pix. Hi-Speed Color Camera
FT-50AW	Amplifier unit
LV-S41L	Reflexionsmodell mit Seitenabtastung
<u>CZ-K1</u>	Digital RGB Sensor
FS-N13CP	Fiber Optic Sensor
FS-N14CP	<u>'</u>
FU-86H	
	





Product	Description
LR-ZB100CP	Distance based laser sensor
<u>GV-H450</u>	CMOS Digital Laser Sensors
<u>AP-33P</u>	Drucksensor für Überdruck
<u>PX-H61</u>	Sensorhead
<u>FW-H07</u>	Sensor Head
<u>LK-HD500</u>	LASER DISP. SENSOR DISPLAY
LR-ZB250CP	connector
SL-VCC10PM	Relay cable
<u>GT2-H50</u>	Messtaster
PZV33P	Selbstjustierender fotoelektrischer Sensor
<u>EM-038</u>	NPN Kleine Näherungsgeber
<u>DH220</u>	
LR-TB2000CL	
<u>GP-M025</u>	Drucksensor
<u>OP-87273</u>	
<u>OP-87285</u>	
<u>OP-87225</u>	Control Cable 5 m
<u>SR-710</u>	
N-R2	Dedicated Communication Unit
<u>OP-87774</u>	Bracket
F-5HA	
FS-V33CP	
<u>FU-16</u>	
GT-H22	
<u>PZ-V12P</u>	
<u>LK-G32</u>	
<u>LK-G82</u>	Laser sensor
<u>LK-G3001</u>	
<u>LK-GC2</u>	
<u>FT-H30</u>	Digital Infrared Temperature Sensor-Head
FT-55 AWP	AMPLIFIER UNİT
<u>FU-32</u>	
<u>SN: 8E510130 LK-G5001PV</u>	HI-SPEED HI-ACCURACY DISP SENSOR
LK-2503/503 (Discontinued)	
<u>SJ-H060A</u>	Bar Type Main Unit
LR-ZB100C3P	Laser sensor with built-in control
<u>OP-84210</u>	
PZ-G42CB	
<u>PZ-G61N</u>	
PZ-G61CN	
<u>FS-V31C</u>	
<u>F-1</u>	Side Detection Lens
KV-24RW-obsolete / Reconditioned	Controller
AP-C40WP	Digital Pressure Sensor
<u>GV-H1000</u>	





Product	Description
CA-DRW10F	Ring light
OP-87442	Power I/O cable (10 m)
CV-L6	camera lens machine vision
FU-57TE	
KV-L21V	Serial communication unit
<u>OP-87903</u>	Sensor head cable 2m
IV-HG10	Sensor Amplifier for IV-HG, Main unit
<u>—————————————————————————————————————</u>	IV-G image sensor I/O cable (3m)I/O cable (3m) for IV Series
FU-7F	FIBRE OPTIQUE TYPE BARRAGE LONG.PORTEE
FS-N13P	Module
IM-6125	
GL-R20H	-
PZ-V11P	Square Reflective Cable Type, PNP
<u>LR-TB2000</u>	Photoelectric Sensor
IL-100	Sensor
<u>IV-G10</u>	Vision sensor (main unit)
OP-87527 /2m/	Control cable
<u>CA-LH25</u>	
<u>OP-87428</u>	VH Stand Adapter
<u>OP-87451</u>	
<u>OP-87905</u>	
<u>OP-87910</u>	IV-G Image sensor bracket
<u>IV-G500CA</u>	Image sensor (20-500mm, AF, colored)
<u>EH305</u>	Smart RGB Digital Sensor
<u>GT2-A32</u>	High precision digital contact sensor
<u>CV-5001P</u>	Digital Image Sensor/Controller
<u>OP-87458 (IV)</u>	Ethernet cable (M12 4-pin / RJ45) NFPA79-compatible Straight cable 5 m
<u>OP-77679</u>	contact for GT
<u>GV-H1000 + GV-21</u>	
SZ-P5NM	Output Cable, 5-m, NPN for SZ-
<u>SR-G100</u>	Model wireless, Bluetooth connection
<u>LV-S71</u>	sensor
<u>EX-V05</u>	Amplifier Unit NPN
<u>EX-416V</u>	Sensor Head
<u>CZ-40</u>	Digital RGB Sensors Head: Spot Type,Long-distance
<u>FU-42TZ</u>	
<u>EH-303A</u>	Abgeschirmt Meßkopf
ES-M2	Näherungsgeber Verstärker
<u>ES-M1</u>	Näherungsgeber Verstärker
<u>OP-87057 - 15meter(wrong cod.)</u>	
<u>FT-H20</u>	Sensor Head
<u>FS-V11P</u>	Fiber Amplifier, Cable Type, Main Unit, PNP
<u>FU – 5FZ</u>	
<u>LJ-V7020</u>	





Product	Description
<u>LJ-V7000P</u>	Laser Profile Sensor(2D) Controller
<u>LJ-VM100</u>	Display output unit
<u>OP-87504</u>	Console Remote (LJV)
<u>XG-035M</u>	
<u>CA-LM0510</u>	
CA-CN10	Camera Cable 10 m
<u>OP-84231</u>	Handheld Controller
<u>OP-26487</u>	
<u>AP-C31P</u>	
<u>EM-038P</u>	Proximity sensor
<u>SJ-M040</u>	STATIC ELIMINATOR, HEAD
<u>XG-200M</u>	
SL-V40HM	Safety Light Curtains
SL-V80HM	Safety Light Curtains
<u>FS-N11P</u>	Fiber Optic Sensor, Amplifier: Cable Type, Main, PNP
<u>FU-4FZ</u>	Fiber Unit Reflective, Tough-Flex Free-Cut 2M
<u>LK-G5001PV</u>	Ultra High-Speed/High-Accuracy Laser Displacement Sensor
<u>LK-H027K</u>	Ultra High-Speed/High-Accuracy Laser Displacement Sensor
<u>CA-U4</u>	Ultra High-Speed/High-Accuracy Laser Displacement Sensor
<u>LK-H2</u>	Ultra High-Speed/High-Accuracy Laser Displacement Sensor
<u>OP-86940</u>	SZ Window Kit
FU-4F	
<u>FT-H50K</u>	temperature sensor head
LV-NH300	Sensor head, Area Thrubeam, High performance
SZ-VB03	
<u>SZ-VH1</u>	
SZ-VNC03	
<u>SZ-VS10</u>	
<u>SZ-VSM</u>	
<u>SZ-VU32N</u>	
<u>LS-9030D</u>	Head: 2-Axis Standard Model Without Monitor Camera
<u>OP-87904</u>	cable
<u>IB-10</u>	
<u>IV-2000MA</u>	Vision-Sensor
<u>FU-57TZ</u>	
<u>FU-E11</u>	
<u>HR-100</u>	Code Reader
<u>BL-601</u>	Ultra Small Laser Barcode Reader, Standard Type, Front Raster
AP-C33WP	Pressure sensor
<u>FU-51TZ</u>	Optical fiber sensor
<u>IL-S100</u>	CMOS Laser Sensor head (70-130mm)
<u>GT2-P12L</u>	Sensor head
<u>OP-87220</u>	E type Mounting bracket for GT2 Series
PZ-V13P	Built-in amplifier photoelectric sensor
	Panel mounting type





Product	Description
<u>CV-X100A</u>	Sensor
<u>TM-065</u>	OPTICAL MEASURING INSTRUMENT (OPTICAL MICROMETER HEAD)
<u>CB-A5(TM)</u>	Cable with connector
<u>LV-N11MN</u>	Amplifier, Cable, Main unit, NPN
FD-M100AYP	Sensor
<u>FU-54TZ</u>	Fiber optic cable
<u>FU-77TG</u>	Transmitting fiber optic device
<u>UD-320</u>	Sensor Head
<u>SR-750</u>	Ethernet-compatible 2D Code Reader, Short-distance Type
<u>SR-H5W</u>	Setup software
<u>OP-87685</u>	IV bracket
<u>PZ-G61P</u>	Built-in amplifier photoelectric sensors
<u>BL-1301</u>	Ultra Small Digital Barcode Reader Standard Type, Front Raster
<u>CV-X150FP</u>	Image Sensor/Controller
<u>CV-E500</u>	Camera Extension Unit for CV-5000/CV-X100 Series
<u>CV-035C</u>	Digital Double-speed Color Camera
<u>OP-87231</u>	Ethernet Cable (UL)
<u>SR-1000</u>	
<u>OP-87866</u>	1D & 2D CODE READER (MOUNTING BRACKET)
<u>LV-NH100</u>	Sensor head, Area Thrubeam, High performance
<u>GT2-A50</u>	
<u>GT2-72P</u>	High precision digital contact sensor DIN rail amplifier
GT2-CH5M	High precision digital contact sensor
DL-PN1	Communication Unit For Sensor
<u>FU-79</u>	Transmissive Fiber Unit
<u>FU-35FG</u>	Reflective Fiber Unit
<u>FU-E40</u>	light guide measuring head, photocell
<u>GL-R60H</u>	Security barrier
<u>GL-R72H</u>	Safety curtain
<u>PZ-M32P</u>	Self-contained photoelectric sensor
LR-TB5000C	
<u>IX-150</u>	Sensor Head 150 mm
<u>IX-1000</u>	MULTI-POINT LASER SENSOR
<u>OP-87903(IX)</u>	Head to Amplifier cable
OP-87906(IX)	cable
<u>LJ-V7001P</u>	
<u>LJ-V7080</u>	
<u>CB-B3</u>	Head - Controller Cable
<u>CB-PN100</u>	
<u>LK-H057</u>	Sensor head
<u>LG-G5001P</u>	2D Laser Displacement Sensor Controller
<u>IV-G300CA</u>	Sensor Head
<u>GV-H45L</u>	Sensor Head Short-distance
<u>GL-RB21</u>	Deadspace-free Bracket





Product	Description
GL-RB01	Adjusting Bracket
GL-RP10PM	Main Unit Connection Cable,
FU-78	Transmissive Fiber Unit
CA-E100	Input unit for area camera
<u>CA-HX200C</u>	HIGH SPEED CAMERA
XG-X2800	
CV-X400F	Supporting 3D/Line Scan Camera controller Controller: 0.47M pixel camera supporting type
IV-HG600MA	Sensor Head, Wide field of view, Monochrome, Automatic focus model
<u>OP-87909</u>	Rear mounting bracket
ET-90	Amplifier Unit NPN
<u>OP-27937</u>	Sensor
<u>GL-RP5P</u>	Safety Light Curtain
PZ-G41CP	Photoelectric sensor
<u>CV-035M</u>	Digital Double-speed Black-and-white Camera
<u>SZ-P5PS</u>	Output Cable
Complete set of SJ-M020+SJ-M200	
AP-C33P	Pressure Switch
<u>SZ-16V</u>	Safety Laser Scanner, Main Unit
AP-C30C	Pressure Sensor
<u>FS-V22R</u>	Fibre Amplifier, Cable Type, Expansion Unit, NPN
<u>PZ-G102N</u>	Square Reflective Cable Type, NPN
SR-PU1	Cable for the SR-G100
<u>OP-88020</u>	AC adapter
SR-LR1	Communication unit (Ethernet / Bluetooth & RS-232C)
<u>SR-B1</u>	
<u>SR-HL1</u>	Mounting support
SR-G100+SR-PU1+SR-HL1+SR-UB1+SR-	
<u>B1+OP-88020</u>	
<u>FS-V12</u>	UNIT-AMP EXPANSION
<u>FS-V31</u>	Sensor
<u>FU-18</u>	Transmissive Fibre Unit
<u>LK-G3000</u>	High-Speed, High-Accuracy CCD Laser Displacement Sensor
<u>LV-NH42</u>	
FS-M1	Fiber Amplifier
<u>LR-TB5000</u>	Laser Sensor
LR-ZH500P	Sensor
<u>PR-MB30P3</u>	Photoelectric Sensor
PR-M51P3	
IL-S025	Sensor head
LV-N11CP	Measuring amplifier
PX-10CP	Amplifier Unit
	SMALL/DUAL SPOT SENSOR
PX-10P	Amplifier Unit
PZ-G52CB	Through-beam Self-Contained Photoelectric Sensor
E66085-H AWM Style 20379 80C VW-1	camera cable
	04.110.14 04.010





Product	Description
<u>OP-87409</u>	Side connection bracket / LR-Z
AP-12S	SENSOR
AP-33P (PNP TYPE)	SENSOR
CA-SD16G	,MEMORY CARD
	CAMERA
reflector for LV-S62	-
FU-66TZ	Reflective Fiber Unit
FS-N41P	
FS-N42P	
FS-N11CP	Fiberoptic Sensor Amplifier FS-Neo with plug connection
CV-5002	
IV-G500MA	
PZ-G101CB	Photoelectric sensor
OP-73864	connecting cable
GL-R79F	Safety Light Curtain
LV-S72	Sensor head
FS-V30	55.155545
<u>CA-LHW16</u>	
CA-CH10R	
<u>PZ-51T</u>	
PZ-51RP	
CA-H048MX	Intuitive Vision System
CA-LH4	High-resolution Low-distortion Len
<u>PZ-G62N</u>	
FU-R67TZ M6	FIBER CABLE
FS-N18N	SENSOR F/O
<u>FS-N43N</u>	SENSOR PHIBEROPTIC
FU-R77TZ M4	FIBER CABLE
XG-HL02M	LİNE
<u>SZ-V32</u>	
<u>OP-87770</u>	Mounting bracket
<u>LR-TB2000C</u>	Laser distance sensor
<u>LR-W500C</u>	Full Spectrum Sensor
<u>CB-A10</u>	
<u>LR-W70C</u>	
<u>IL-S065</u>	
<u>CB-B10</u>	Cable with connector
<u>CV-X350F</u>	
CA-DC40E	
<u>CA-H500M</u>	
<u>CA-H200M</u>	
<u>CA-DSW7</u>	
<u>CA-DRR8M</u>	
<u>CA-DRW13M</u>	
<u>CV-H200C</u>	





Product	Description
GP-M010(8A)	
<u>LJ-V7060</u>	
OP-87445 (IV)	
<u>OP-87459 (IV)</u>	•
LV-NH32	
<u>GL-R56H</u>	Safety Light Curtain
<u>GL-R08H</u>	, i
<u>FD-R80</u>	•
LR-ZB240CB	
GL-RP10P	
KEY.FS-N41C	
FU-35TG 10153246	
KEY.CA-CN3	CAMERA CABLE
KEY. CA LH8	8MM CAMERA LENS
KEY. XG-8500L	
KEY. XG-HL02M	LINE SCAN CAMERA
KEY. CA-LHW8	CAMERA LENS
KEY. CA-CH10	CAMERA CABLE
KEY. OP84231	REMOTE CONSOL
TM-H1X	
<u>LK-H080</u>	
LJ-H3	
<u>CA-DXW7</u>	
<u>CA-DRW8M</u>	
<u>FU-85A</u>	OPTICAL FIBER SENSOR
<u>FS-N44P</u>	
PR-FB30CP	PHOTOELECTRIC SENSOR
<u>TM-3000P</u>	
<u>XG-X2500</u>	
CA-LHR16	
<u>CV-X400A</u>	
<u>CV-X470F</u>	
<u>CA-H2100</u>	
<u>CA-H5</u>	
<u>CA-200M</u>	
<u>CA-H2100M</u>	
<u>CV-X450F</u>	
GL-T11R	
PZ-G101CP	SENSOR
<u>CV-X480F</u>	
CA-E100LJ	
<u>LJ-V7200</u>	
<u>LJ-V7300</u>	
<u>CA-CH17R</u>	
LR-ZB100P	Self-contained CMOS Laser Sensor





Product	Description
CA-CN10L	
PRM51N3	Transmissive Cable
GL-R32H	
GL-R4-4H	
GL-RP1OP	
<u>CA-H200C</u>	
<u>CA-H2100C</u>	
FU-84C (5000) FS-V31P, F-2	
<u>GL-R127F</u>	safety light curtain
PZ-G42CP	Photoelectric sensor
GL-R36H + GL-RC20 + GL-RPC03P + GL-RB01	light curtain set
FU-22X	Light guide device, reflective
<u>FU-66</u>	reflective light guide device
<u>CA-H500MX</u>	
<u>BL-180</u>	
<u>CB-B5</u>	
<u>LK-G87</u>	
<u>LK-G157</u>	
LK-G3001PV	
LK-GC10	
<u>LK-GC5</u>	5 meters cable
<u>LS-7070</u>	
<u>LK-G507</u>	
<u>IV2-G500MA</u>	Image sensor
<u>CB-EP100</u>	
<u>CB-B10E</u>	
<u>LS-D501</u>	
<u>KV-7500</u>	PLC
<u>KV-B16TCP</u>	Block terminal
KV-C16XTD	PLC card
KV-SC20V	Counter card
KV-L20V	Network card
<u>GL-R16H + GL-RB01 + GL-RPC03N</u>	
<u>LS-C3AM</u>	
<u>LS-S11</u>	
<u>LS-H1W</u>	
<u>LS-7070M+LS-7601</u>	
<u>CV-X420F</u>	Controls
<u>CA-H048C</u>	camera
CA-H048CX	camera
IV2-CP50	Control Panel
IV2-G300CA	Image Sensor
IV2-G30F	Laser sensor AMP main unit
<u>OP-87443</u>	Display Power Cable (2m)
GL-R12H	





Product	Description
LR-X100C	Description
CB-NPN20E	
<u>CB-C5R +TM-X5065 +TM-X5000</u>	
FD-Q20C	
IV2-G600MA	sensor
OP-87444 5MT.	PANEL POWER CABLE
OP-87458 5MT.	STRAGHT CABLE
DL-DN1	DEVICE NET TM SUPPORT
GL-RPC03P	BEVIOLINET TWO GOTT CITY
SR-X300	
SR-2000	
SR-2000W	
IV2-G500CA	
OP-87444	
<u>OP-87528</u>	Control cable
CA-H500C	5mpx camera
LJ-X8200	op./. dad
LJ-X8000	
TM-3001P+TM-040	
SZ-VU32	
SZ-VP5	
SZ-VS5	
SZ-VB12	
<u>EX-V01P</u>	
FD-Q10C	
CA-DSW30	White Back Light
GT2-72P 189272P 4E410104	
GT2-CH10M	
CA-AD1	
<u>CA-H1DB</u>	
SZ-V32N	Domain browser
<u>GL-R52H</u>	Safety barrier (light curtain)
CA-H200MX	Image module
CA-DC60E	Led Controller
PS-46	
<u>IV3-G120</u>	
<u>OP-88649</u>	
IV3-G600MA	·
CA-DRM10X	
SZ-VH1X	2D OPTICAL SENSOR - SZ-VH1X TESTA SCANNER CON TELECAMERA
<u>IV3-500Ca</u>	
<u>LS-7001</u>	CONTROLLER
AMFI IV-G 10	SENSOR
<u>CA-D10</u>	





Product	Description
CA-DDW15	LED LIGHT
FS-N41C	LED LIGHT
IV3-G600CA	
PZ-M63P	
FS-V21	Sensor
CA-HX500M	Serisor
<u>OP-88639</u>	SENSOR
<u>FW-H02</u>	
LR-ZB90CB	LAZER SENSOR
XG-7501P	CAMERA AMPLIFIER
CA-H500C (one time special price)	
CA-HL-04MX	
CA-LHE35	
CA-E200L	
CA-CF5	
<u>IX-360</u>	LASER SCANNER
<u>FT-50AWP</u>	
<u>LK-G37</u>	
<u>LK-G407</u>	
<u>LK-F1</u>	
<u>LK-F2</u>	
<u>LK-G502</u>	
<u>FS-N43P</u>	AMPLIFIER
<u>FU-1623</u>	OPTICAL FIBRE
<u>LK-H052</u>	Sensor head
<u>LK-H082</u>	
<u>LK-H152</u>	
<u>LK-H087</u>	
<u>LK-H157</u>	
<u>CB-A5</u>	
<u>CB-A20</u>	
<u>CB-A5E</u>	
<u>CB-A10E</u>	
<u>LK-F3</u>	ND Filter
FD-M50-ATP	FLOW-SENSOR
<u>LK-H052K</u>	
<u>CV-5501P-PNP</u>	CONTROL UNIT
GL-R28H	Sensor Bariyer
<u>DD-860</u>	DOUBLE PLATE SENSOR TOOLING
LR-ZB250AP + LR-ZB250CP	SENSOR
GL-R32L	
GL-RB11	
GS-73PC	
<u>GS-P12C20</u>	
<u>OP-87641</u>	





Product	Description
FT-50AP-18650 AP PNP	·
FT-H50K-186H50K	SENSOR
FS-V21R (NPN)	sensor
GL-R80H	
LK-H1W	
CA-CHX10U	Repeater for camera cable extension
CA-LH75	75mm low distortion and high resolution lens
CA-CH10X	10 m high speed camera cable for repeater
 CA-035M 2MP	0 1
CV-X300F	
CA-CH10BP	
PR-F51P3	
 LJ-X8020	
LJ-X8060	
<u>CA-MP120</u>	
SEN 2021060005 LR-W500C	SENSOR
CA-DRW20X	illuminationequipment
CA-DC50E	control
<u>CA-D10X</u>	connectingcable
CA-LHE12	lens
PZ-V31	<u> </u>
IV3-CP50	IV3 Control Panel
IV3-LG6C	IV3-G Extra Lighting
OP-87458	IV3 Communication Cable 5m
OP-88646	Polarized Filter
CB-B20E	
<u> </u>	
IM-8030T	
LR-ZB100CN	
SR-X100	barcode scanner camera
EX-VO2P	
EX-VO1P	
<u>FD-H32</u>	
<u>AP-C31</u>	Pressure sensor
<u>PZ-51R</u>	Photoelectric Switch
FD-XA1	Flow sensor
OP-88292 / PEL-40	FLOW SENSOR
FD-MA5AP	
FD-XC1R2	
<u>GL-RS05*2</u>	
GL-RP10P*2	
<u>GL-R119F</u>	
LR-ZB250C3P	
<u>OP-87404</u>	
<u>FU-53TZ</u>	





Product	Description
LR-XH50	·
FS N41COP 88245	
LR-ZH500C3P	
LR ZH500CP	
LR-W500C-OP-88021	
<u>FUR77TZ</u>	
GT2-P12	Stylus type General-purpose Sensor head
GL-RB01*4	
GL-R39F	
<u>GL-RS05</u>	
<u>OP-88021</u>	
GL RB01	
GP-M010	Heavy Duty Type Digital Pressure Sensor
PZ-V31P	Photoelectric sensor
BL-R7	MOTOR-BARCODE SCANNER
LK -G5001P	
CA-DRM20X	
CA-D10MX	
<u>EZ-18M</u>	
<u>LK-2001</u>	
GS-M51P	Holding force 500N M12 Connector type Standard type PNP
GS-MA5M	Coding level Low Actuator for GS-M5 Series
<u>GS-51PC</u>	Power to Release Safety Switch Kit
GL-R16H	
<u>GL-R1UB</u>	
<u>FR-S01</u>	
<u>EM-080</u>	SLOT COUNT SENSOR
GL-R88H	
<u>IG-1500</u>	
<u>LR-WA1</u>	
LR-ZH490CB	
<u>GS-P8C10</u>	
GS-11PC	
<u>FS-N41N</u>	
<u>PX-H71 (10M)</u>	PHOTOELECTRIC SENSOR HEAD
PX-H71TZ	
<u>LV-NH35</u>	
IV3-G500CA	IMAGE SENSOR
<u>OP-88642</u>	POLARIZED FILTER (COLORED)
<u>AP-34P</u>	
<u>LK-G3000P</u>	LASER DISPLACEMENT SENSOR
<u>FU-A100</u>	Fibre Unit Thrubeam type
<u>SZ-VP10</u>	Power cord
<u>SR-X100W</u>	With Cable and Brackets of Series (SET)
<u>LV-NH47</u>	SENSOR





Product	Description
<u>GT2-P12K</u>	precision Sensor head
GT2-P12KL	Stylus type High-precision Sensor head (Low measuring force type)
<u>NE-V08</u>	ETERNET SWITCH
<u>OP-75722</u>	Connector Cable
<u>CV-X100M</u>	WIDTH CAMERA CONTROLLER
<u>CV-5000</u>	CABLE
<u>CA-E800</u>	ADDITIONAL CAMERA MODULE
CA-EC80L	CAMERA INPUT MODULE
<u>FU-2303</u>	OPTICAL FIBRE
<u>CA-CN17</u>	CAMERA CABLE
<u>SZ-VU04</u>	CONTROL UNIT
<u>SZ-VS20 20M</u>	COMMUNICATION CABLE
<u>NR-600</u>	DATA CONTROLLER
PZ-G42EP	
<u>LJX8000A</u>	
<u>SZ-VHW</u>	Safety Window